

IGNO NON-COMBUSTIBLE PEDESTALS



Archatrak IGNO paver supports permit the construction of totally non-combustible elevated decks on rooftops or other locations where strict fire regulations are enforced.

The solid steel supports are completely fireproof, yet can provide incremental height adjustment from as low as 1" to a maximum of 20". The 6 1/4" x 6 1/4" totally flat steel base distributes the load evenly over roofing membranes, but an optional 9" x 9" buffer pad can be supplied if required. A locking ring on the screwed column prevents any movement and ensures excellent stability.

Key benefits include:

- Will not catch fire, create smoke, or spread flames
- High load bearing - over 2200lb
- Will not crack, split or warp
- Zinc nickel finish offers excellent corrosion resistance
- Easy to install and adjust height
- Externally threaded tube with locking ring for absolute stability
- Cost effective - comparable in price with plastic pedestals
- Only 3 components - base with column, header, head cap



SPECIFICATIONS

Material:	Mild steel
Finish:	Zinc nickel anti-corrosion
Head diam.:	3 3/4"
Base size:	6 1/4" x 6 1/4"
Loading:	2200lb +
Head tabs:	1 1/8" thick, 1/2" high
Fire rating:	(EN13501-1): A1-Afl

HEIGHT RANGE

RP-FR-1	1" - 1 3/8"
RP-FR-2	1 3/8" - 2"
RP-FR-3	2" - 2 3/4"
RP-FR-4	2 3/4" - 4 1/2"
RP-FR-5	4 1/2" - 8"
RP-FR-6	8" - 12"
RP-FR-7	12" - 16"
RP-FR-8	16" - 20"

